



◆ストレート形

RoHS 指令対応品

呼 び		呼 び	各 部 の 寸 法									標準色	適合電線範囲		適合工具	一箱入数
規格	ビニル	規格	ナイロン	d ₂	B	φd ₁	F ₁	l ₂	l	L ₁	板厚		撚線mm ²	AWG		
	AVF0.08-3		—	3.2	5.2	2.2	5.9	9.5	12.5	18.0	0.8	黄※	0.08	28	DS05N DH-1B	1,000 (100×10)
	AVF0.08-V3.5		—	3.7	5.7		7.7		15.0	20.5						
UL	AVF0.3-2		—	2.2	5.2	2.2	5.9	9.5	12.5	18.0	0.65	黄※	0.1 ~ 0.3	26-22	*DS05N *DH-1B *DS-A5 PALM-032A	1,000 (100×10)
UL	AVF0.3-3		—	3.2												
	AVF0.3-V3.5		—		5.7		7.7									
	AVF0.3-L3.5		—	3.7			6.7		15.0	20.5						
UL	AVF0.3-3.5		—		6.6		7.7									
UL	AVF0.3-4		—	4.3												
UL	AVF0.5-2	APF0.5-2		2.2	5.2	2.2	5.9	9.5	12.5	18.0	0.5	黄※	0.3 ~ 0.5	22-20	*DS05N *DH-1B *DS-A5 PALM-032A	1,000 (100×10)
UL	AVF0.5-3	APF0.5-3		3.2			7.7									
	AVF0.5-V3.5	APF0.5-V3.5			5.7		6.7									
	AVF0.5-L3.5	APF0.5-L3.5		3.7			7.7		15.0	20.5						
UL	AVF0.5-3.5	APF0.5-3.5			6.6											
UL	AVF0.5-4	APF0.5-4		4.3												
UL	AVF0.5-5	APF0.5-5		5.3	8.0		7.0									
UL	AVF1.25-M3	APF1.25-M3		3.2	5.6		5.0	9.5	14.2	19.2	0.8	赤※	0.5 ~ 1.65	20-16	*DS-Hi3 *DS-Hi34 *DS-Hi34S *DH-1B *DS-A5 PALM-032A	500 (100×5)
UL	AVF1.25-3	APF1.25-3			6.0		4.4		15.2	20.2						
	AVF1.25-V3	APF1.25-V3			5.7		6.3		15.6	20.6						
UL	AVF1.25-L3	APF1.25-L3			5.9		6.5		12.8	17.8						
UL	AVF1.25-C3.5	APF1.25-C3.5		3.7	6.0	3.3	4.5	9.5	13.5	18.5	0.8	赤※	0.5 ~ 1.65	20-16	*DS-Hi3 *DS-Hi34 *DS-Hi34S *DH-1B *DS-A5 PALM-032A	500 (100×5)
UL	AVF1.25-S3.5	APF1.25-S3.5			5.7		6.3		14.2	19.2						
UL	AVF1.25-3.5	APF1.25-3.5			6.0		4.4		15.2	20.2						
UL	AVF1.25-V3.5	APF1.25-V3.5			5.7		6.3		15.6	20.6						
UL	AVF1.25-L3.5	APF1.25-L3.5		4.3	5.9		6.5	9.5	15.4	20.4	0.8	青※	1.04 ~ 2.63	16-14	*DS-Hi4 *DS-Hi34 *DS-Hi34S *DH-1B *DS-A5 PALM-032A	500 (100×5)
UL	AVF1.25-A3.5	APF1.25-A3.5			6.4		6.8		15.6	20.6						
UL	AVF1.25-S4	APF1.25-S4			7.0		6.5		16.2	21.2						
UL	AVF1.25-4	APF1.25-4			8.3		7.1		17.2	22.2						
UL	AVF1.25-A4	APF1.25-A4		5.3	8.0		7.0	9.5	17.0	22.0	1.0	黄※	2.63 ~ 4.6	12		400 (100×4)
UL	AVF1.25-5	APF1.25-5			9.7		7.6		20.2	25.2						
UL	AVF2-3	APF2-3			5.5	3.9	4.4	9.5	14.2	19.2						
UL	AVF2-A3	APF2-A3			5.7		6.1		15.7	20.7						
UL	AVF2-S3.5	APF2-S3.5			6.5		6.0		15.8	20.8						
UL	AVF2-3.5	APF2-3.5			6.4		6.7		15.6	20.6						
UL	AVF2-M4	APF2-M4		4.3	6.6	3.9	8.0	9.5	15.8	20.8	0.8	青※	1.04 ~ 2.63	16-14	*DS-Hi4 *DS-Hi34 *DS-Hi34S *DH-1B *DS-A5 PALM-032A	500 (100×5)
UL	AVF2-S4	APF2-S4			6.9		7.2		16.2	21.2						
UL	AVF2-4	APF2-4			8.3				17.2	22.2						
UL	AVF2-A4	APF2-A4			8.5		8.5		20.2	25.2						
UL	AVF2-5	APF2-5		6.4	11.0		9.5	9.5	17.2	22.2	1.0	黄※	2.63 ~ 6.64	12-10	*DS-Hi5 *DH-1B *DS-A5	300 (100×3)
UL	AVF2-6	APF2-6							23.5	31.2						
UL	AVF3.5-4	APF3.5-4			4.3	5.4	7.9	14.0	19.5	27.2						
UL	AVF3.5-5	APF3.5-5			5.3		7.2		18.0	25.7						
UL	AVF5.5-M4	APF5.5-M4			7.1		8.5		19.0	26.7						
UL	AVF5.5-4	APF5.5-4			8.5		10.5		23.5	31.2						
UL	AVF5.5-5	APF5.5-5		5.3	9.0				24.5	32.2						
UL	AVF5.5-6	APF5.5-6		6.4	12.5											
UL	AVF5.5-8	APF5.5-8		8.4	15.0											200 (100×2)

1. 各呼びの印は、UL登録品、CSA登録品です。

2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。

3. 上記寸法表にかぎらず特注品もご相談ください。

4. *印はUL適合工具です。

※…表の絶縁被覆のカラーは、あくまで標準色です。ご用意できるカラーはP. 20を参照下さい。





