
銅線用絶縁被覆付圧着端子 丸 形 端 子 〈RAV形〉〈RAA形〉





◆ストレート形

RoHS2指令対応品

呼び												煙	適合電	 線節囲	1101102	日下刈心面
 規 格		 各	ビニル	φ d ₂	В	ϕd_1	F ₁	l 2	l l	Lı	板厚	標準色	燃線mm²	AWG	適合工具	一箱入数
	(l)		RAV3.5-S4		7.0			17.1	25.8							
	(4)	(II)	RAV3.5-4	5.3			8.3	14.0			1.0	黄※		12	*DS-Hi5 *DH-1B	300 (100×3)
	(4)	(1)	RAV3.5-5		8.5				17.8	26.5			2.63			
	(4)	(B)	RAV3.5-6	6.4	8.4	4.9	10.5		21.8	30.5			S			
	(4)	(B)	RAV3.5-8	8.4		10.5	12.5	25.0	33.7			4.6	.6	*DS-A5		
	(4)	(I)	RAV3.5-10	10.5		12.0	25.0	33.7								
	(4)		RAV3.5-12	13.0	20.0	.0	15.7		31.0	39.7						200 (100×2)
	(h)	(II)	RAV5.5-V3	3.2	7.2		5.9		15.8	23.5						
	(4)	(I)	RAV5.5-M3		7.1		8.5		18.3	26.0						
	(4)	(II)	RAV5.5-V3.5		7.2		5.9		15.8	23.5						
	(4)	®	RAV5.5-3.5		7.7		7.2		17.3	25.0						
	(4)	(II)	RAV5.5-M3.5		7.1		8.5		18.3	26.0						
	(4)	(II)	RAV5.5-V4	4.3	7.2		5.9		15.8	23.5						
	(4)	(B)	RAV5.5-S4	4.4	7.7		7.2		17.3	25.0						300 (100×3)
			RAV5.5-N4		8.0				18.8	26.5						
	(4)	(B)	RAV5.5-M4	4.3	7.1				18.3	26.0						
(II)	(4)	®	RAV5.5-4 (RAA5.5-4)		9.5		8.5		19.5	27.2			2.63		*DS-Hi5	
	(4)	(II)	RAV5.5-S5		8.0				18.8	26.5						
(IS)	(4)	(II)	RAV5.5-5 (RAA5.5-5)	5.3	9.5	5.4		14.0	19.5	27.2	1.0	黄※	5	12-10	*DH-1B	
	(4)		RAV5.5-L5		12.0	-	10.2	-	22.5	30.2			6.64		*DS-A5	
	(4)		RAV5.5-S6		9.5		8.5		19.5	27.2						
(II)	(4)	®	RAV5.5-6 (RAA5.5-6)	6.4	12.0		10.2		22.5	30.2						
	(4)		RAV5.5-L6	8.4		15.0	14.0		26.3	34.0						200 (100×2)
	(4)		RAV5.5-A6		15.0		16.0		29.8	37.5						
<u>(II)</u>	(4)	(B)	RAV5.5-8 (RAA5.5-8)				14.0		27.3	35.0						
(II)	(4)	(II)	RAV5.5-10 (RAA5.5-10)													
	(4)		RAV5.5-12	13.0	20.0		15.7		32.0	39.7						
	(4)		RAV5.5-14	15.0												
	(4)		RAV5.5-16	17.0	32.0)	25.7		48.0	55.7						100
	(4)		RAV5.5-20	21.0												

- 1. 各呼びの印は、JIS規格品、UL登録品、CSA登録品です。() はJIS規格品の呼びを示します。
 2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。
 3. 上記寸法表にかぎらず特注品もご相談ください。
 4. *印はUL適合工具です。
 ※…表の絶縁被覆のカラーは、あくまで標準色です。ご用意できるカラーはP.20をご参照下さい。